203MVL, 204MVL



203MVL



204MVL



203MVLM

FEATURES & BENEFITS

- Two Star Generation IV LEDs
- Twenty-six customer selectable flash patterns, including Steady-On and Cycle All
- Long life LEDs, rated for up to 100,000 hours
- Compact and powerful LED light output
- External pattern select wire (permanent mount only)
- Twist on/off lens
- Durable ABS plastic base
- Durable polycarbonate lens
- Flange permanent mount or magnet mount
- UL listed
- Durable polycarbonate lens
- Flange permanent mount, or magnet mount (203MVLM)
- Pipe mount no longer available for 204MVL
- Voltage: 10-110V DC
- Amp draw: 0.35 amps @ 12V DC, 0.13 amps @ 110V DC
- Colors:
- Approvals 203MVL: SAE Class II (Amber)*, SAE Class III (Blue)*
- Approvals 204MVL: SAE Class II (Amber)*,

* does not apply to all flash patterns

PART	DESCRIPTION
203MVL	3 ½"H, LED Beacon, flange mount, 10-110V DC
203MVLM	3 ½"H, LED Beacon, magnet mount with cig. plug, 10-110V DC
204MVL	5"H, LED Beacon, flange mount, 10-110V DC

⚠ Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

FOR MORE INFORMATION
VISIT OUR WEBSITE.
STARSAFETYTECHNOLOGIES.COM

Star Safety Technologies, LLC
455 Rochester St., Avon, NY 14414
Phone: 585-226-9500 | Fax: 888-478-2797

STAR Safety Technologies by Grote