DLXTH SERIES











FEATURES & BENEFITS

- Thirty-six high intensity LEDs
- Twelve customer selectable flash patterns in two phases plus Steady-On
- Circuitry is fully encapsulated within housing and is designed with a breathable membrane pad to reduce condensation
- Over-molded wire seal and strain relief
- S-Link 2.0 System[™] synchronizing capabilities with other Star LED units
- Can be mounted just about anywhere, interior or exterior

- Can be mounted in a bezel, grommet, or window mount
- Split colors available
- Also available with weatherproof connector pre-installed on heads
- Dimensions: DLXTHU 7 1/4"L x 3"H, DLXTHR 4"Dia.
- Voltage: 12/24V DC
- Amp draw: .3 amps (average)
- Color combinations: C = Clear lens

DLXTH - C C C C











	_	
DLXTHUS -		

PART	DESCRIPTION
DLXTHR-1-*	4" Round, bezel, flashing
DLXTHR-2-*	4" Round grommet, weatherproof connector, flashing
DLXTHR-4-*	4" Round, grommet, flashing
DLXTHR-8-*	4" Round, grommet weatherproof connector, flashing
DLXTHU-1-*	6" Oval, bezel, flashing
DLXTHU-2-*	6" Oval, weatherproof connector, flashing
DLXTHU-4-*	6" Oval, grommet, flashing
DLXTHU-7-*	6" Oval, window bezel, flashing
DLXTHU-8-*	6" Oval, grommet and weatherproof connector, flashing
DLXTHUS-1-**	6" Oval, split color, bezel, flashing
DLXTHUS-4-**	6" Oval split color, grommet, flashing

Marning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF138 Rev-G 09-07-2023





LED DLXTH MODEL NUMBER GENERATOR



DL_TH_-





Rubber Grommet







Flush Mount Bezel

PATTERN

X = Flashing

N = Steady Burn

SERIES—

R = 4" round

U = oval

MOUNT TYPE -

1 = Flush mount bezel

2 = No mount (lighthead only)

4 = Rubber grommet

7 = Window bezel

8 = Rubber grommet with weatherproof connector

PLATING ———

- = Black

C = Chrome

COLOR -

 $A = Amber \\ W = Cool White \\ R = Red \\ BC = Blue LED Clear Lens \\ BC = Green LED Clear Lens \\ BC = Red LED Clear Lens$

Marning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF138 Rev-G 09-07-2023



