



STAR HEADLIGHT & LANTERN CO.

240



240CF



240SF



240C

Specifications and Features

- Star X-Fire® technology
- 12 different selectable flash patterns in either of two phases, plus steady-on
- S-Link System™ synchronizing capabilities with other Star LED units, hardwire only
- Extremely low current draw
- RFI protection
- Rugged die-cast base is fully gasketed
- Permanent mount, 1" pipe mount, flange mount, magnet mount
- Dimensions: short lens - 4 1/4"H x 5 1/2"Dia., tall lens - 6"H x 5 1/2"Dia.
- Voltage: permanent - 12-24V DC, magnet - 12V DC
- Amp draw: 0.5A @ 12V DC, 0.3A @ 24V DC
- Lens color:
- Approvals: SAE Class I (Amber, White short and tall)

Model Numbers/Descriptions:

240C	LED beacon, tall lens, permanent mount
240CF	LED beacon, tall lens, flange mount
240CM	LED beacon, tall lens, magnet mount
240S	LED beacon, short lens, permanent mount
240SF	LED beacon, short lens, flange mount
240SM	LED beacon, short lens, magnet mount

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF001 Rev D 10-25-2021

STAR
WARNING
SYSTEMS®

STAR SIGNAL
VEHICLE PRODUCTS®

Star Headlight & Lantern Co., Inc.

455 Rochester Street
Avon, NY 14414
Phone: 585-226-9500
Fax: 888-478-2797
starheadlight.com

BRADFORD
Vehicle Solutions Inc.™



PROUDLY MADE IN THE U.S.A.
An ISO 9001:2015 Certified Company