## WHITE NOISE **BACKUP ALARMS**







VOLTAGE






CONSTRUCTION

VOLTAGE: 12-24 VDC

AMP DRAW (73340, 73450, 73470): 0.4A @ 14VDC AMP DRAW (73460): 0.16A @ 14VDC **MATERIAL: GLASS FILLED NYLON OPERATING TEMPERATURE:** -40°C TO +85°C















White Noise Backup Alarms prioritize safety without causing unnecessary disturbance to those nearby the work site.

## REDUCE NOISE POLLUTION WITHOUT COMPROMISING SAFETY

Grote's "White Noise" backup alarms address concerns associated with traditional alarms in busy work areas. By emitting sound across multiple frequencies, these alarms tackle noise pollution effectively.

This design ensures individuals in the danger zone around reversing vehicles are adequately warned, while keeping overall noise levels in check. This makes them an ideal choice for bustling work environments.



## **FEATURES & BENEFITS**

- "White Noise" function reduces noise pollution (ideal for use in residential areas)
- Rugged construction with glass-filled nylon housings
- Universal mounting options for simple installation and replacement
- Rear facing design provides protection for the speaker from the elements ensuring durability

PART	DESCRIPTION	DECIBELS	APPROVALS
73340	BACKUP ALARM, MULTI FREQUENCY, "WHITE NOISE", STANDARD MOUNT	97 dB	SAE J994 TYPE C
73450	BACKUP ALARM, MULTI FREQUENCY, "WHITE NOISE", REVERSE MOUNT	97 dB	SAE J994 TYPE C
73460	BACKUP ALARM, MULTI FREQUENCY, "WHITE NOISE", REVERSE MOUNT	102 dB	SAE J994 TYPE F
73470	BACKUP ALARM, MULTI FREQUENCY, "WHITE NOISE", REVERSE MOUNT	107 dB	SAE J994 TYPE A

▲ Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



Star Safety Technologies, LLC 455 Rochester St., Avon, NY 14414

Phone: 585-226-9500 | Fax: 888-478-2797

