

SCHOOL BUS SAFETY KITS

FROM GROTE



AUXILIARY LED WARNING LIGHT KITS

The new Auxiliary LED Warning Light system from Grote is *specifically* designed for school buses, significantly increasing the safety of children as they board or leave the bus when it is stopped. It enhances the two red LED lights located above the front and rear bumpers, making it easier for motorists to recognize a stopped school bus. Additionally, the added flasher can be used on other vehicles in your fleet, such as service trucks.







79327 | CONSTELLATION® KIT EASY PLUG-IN INSTALLATION

Kit includes:

- BKDLITE-RR: LED Directional Lights, 6-Diode, Class I, Red (x4)
- BKLD418-2: Control Box (x2)
- SWH-346-2: Wire Harness (x2)
- SWH-346-5: Wire Harness (x2)
- 60 ft. 2-conductor cable
- All hardware: fuse holder, fuse, weather-tight connectors, ties



79329 | DUMMY HEAD KIT

Kit includes:

- 4 Red dummy heads (lights)
- 60 ft. 3-conductor cable
- All hardware: Heat shrinkable butt connectors, tie wraps, adhesive cable tie holders
- Tie in to existing warning lights on the bus

EMAIL OR FAX YOUR ORDER: CUSTOMERSERVICECA@GROTE.COM | 1.800.267.9024




SCAN THE QR CODE TO CHECK OUT THE VIDEO

COMPANY

CONTACT NAME

P0 #





SCHOOL BUS SAFETY KITS

FROM GROTE

78031

73040





240SFL-C

LED BEACON, UNIVERSAL MOUNT, CLASS II. WHITE

- Star Generation IV LEDs
- 26 customer selectable flash patterns, plus steady-on
- Shipped in a quad flash pattern
- Extremely low current draw
- Rugged die-cast base is fully gasketed
- Permanent mount, 1" pipe mount, flange mount, magnet mount



LED BEACON, PERMANENT MOUNT, CLASS I. WHITE

- 12 different selectable flash patterns in either of two phases, plus steady-on
- Extremely low current draw
- Durable polycarbonate twist-on/off lens
- S-Link™ allows for flash pattern synchronization with up to six other S-Link compatible units
- Flanged 3-hole permanent mount, 1" pipe mount, vacuum magnet mount with aux. plug



78851

LED BEACON, PERMANENT MOUNT, CLASS II. WHITE

- 26 selectable flash patterns, plus steady-on
- Conformal coated Circuit board protects circuitry
- Durable, lightweight polycarbonate base, flanged 3-hole permanent mount, 1" pipe mount, vacuum magnet mount with aux. plug



64M11-5

LED RADIUS LIGHTS, PROPRIETARY WIDE FLOOD

- Tough, durable, and lightweight cast aluminum housing
- Six-200 lumen LEDS that produce daylight-like visibility
- TIR Lens for efficiently distributed lighting
- Bi-Voltage System for 12 volt and 24 volt systems
- Vibration, dust, corrosion, and moisture resistant



STANDARD TONE BACKUP ALARM, MEDIUM DUTY. 97dB

- Rugged construction w/ glass-filled nylon housings
- Universal mounting incl. grommet mounted products
- Select the output volume based on the ambient noise levels of the environment where the alarms will be in use





6" OVAL LED STROBE LIGHT WITH S-LINK SYNCHRONIZATION, WHITE, 12V/24V

- Grommet mount can be converted to surface mount with optional chrome or black bezels
- 12 different selectable flash patterns in either of 2 phases plus steady-on
- S-Link™ allows for flash pattern synchronization with up to six other S-Link compatible units





64G11/64G01

TRILLIANT® T26 LED WORK LIGHTS, PENDANT MOUNT

- Efficient light engine projects 1400 effective Lumens using only 17.5 Watts of power across 10-48 Volts
- Small size combined with tough construction allows mounting in places where larger or less rugged lamps cannot fit or survive
- Advanced circuit design provides electronically quiet operation; protects against EMI without interfering with other electronic devices

78142



6 DIODE LED DIRECTIONAL LIGHT, CLASS I, RED

- Ultra-low profile
- 12 different selectable flash patterns in either of two phases, plus steady-on
- Robust design, die-cast aluminum base
- Standard four wire hook up (power, ground, pattern, sync)
- S-Link™ System allows for flash pattern synchronization with up to six other S-Link compatible units

EMAIL OR FAX YOUR ORDER: CUSTOMERSERVICECA@GROTE.COM | 1.800.267.9024



FOR MORE INFORMATION VISIT OUR WEBSITE. GROTE.COM

COMPANY

CONTACT NAME

P0 #

